RC50A21S-4KSM

TV LED RCA 50 4K ULTRA HD SMART ISDBT 1+8 (A/M CON CONTROL DE VOZ) CON BLUETOOTH

Cosmetic

Color of Front Cabinet	Glossy Black		
Color of Frame	N/A		
Color of Middle Cabinet	Matt Black		
Color of Back Cabinet	Matt Black		
Color of Base Stan	Glossy Black		
LED Indicator color/LED	RED (Standby) BLUE (ON)		
Logo Indication/Logo	N/A		
Number of Key/	5 keys		
VESA Wall Mounting Hole	200*200(mm)		
Border Width	Top：13，bottom：21，Left：14，Right：14		
power cable Length	1.5m , 2pin		
Drop Standard	Chinese standard		

Material

Front Cover	plastic		
Frame	N/A		
Middle Cover	Metal		
Back Cover	plastic		
Stand	plastic		
Carton	Brown corrugated Paper		
Package	PO bag		
Cabinet Request	☑ ROHS	☐ V0 FIAME RETARDATION	
Certification	N/A		

Product Info

EAN Bar code:	7453021616249		
	W (mm)	H (mm)	D (mm)
Size of Unit (without Base):	1125	652	88
Size of Unit (with Base):	1125	702	268

DISPLAY

Backlight Type	DLED
Active Area	1095.84(H) × 616.41(V) (50")
Aspect Ratio	16:9
Resolution	3840x2160
Refresh Rate	60Hz
Luminance	200 cd/m²±10%
Contrast Ratio	4000:1
Display Colors	16.7M
Response Time	8ms
View Angle	178H/178V

FEATURES

Chipset	MT5522
OSD Language/OSD	English, Spanish
Sleep Timers	No
Auto Shut off	Yes
Hotel Mode	NO
Max Storage Channels	ATV:99CH DTV:700CH(DVB-T+DVB-C)\3500CH(DVB-S/S2)
HDMI Version/HDMI	1.4/2.0 HDCP Version:1.4/2.2 ☑ CEC ☑ ARC
USB Chanel Function/USB	SW Upgrade、Multimedia
other	EPG, Subtitle ☐ TELETEXT ☐ NICAM

SMART SYSTEM

CPU	4 x Core A53
GPU	4 x Malli450
RAM	1.25GB
FLASH Memory	8GB
WIFI	2.4G,Support 802.11b/g/n
Ethernet	10M/100M
Android	7.0
App	Media Center,File Manager

TV SYSTEM

TV Input	ATV:NTSC, DTV:ISDB-T
Video System	ATV:M/N,MTS DTV:MPEG-2,MPEG-4,H.264
Sound System	ATV:M/N DTV:MPEG-1 layer 1/2,MPEG-2 layer 2
Component Video Format	480i, 480p, 720p, 1080i, 1080p
PC Video Format	max 1920x1080@60Hz
HDMI Video Format	480i, 480p, 720p, 1080i, 1080p, 2160P,3840×2160@60HZ

USB Connection/USB	Photo	jpg/jpeg/bmp/png
	Movie	avi/mpg/mov/ts/mkv/dat/mp4/vob/rm
	Music	mp3/aac/m4a
	Text	txt

DVD Combo Format/DVD	No

Picture

Color Temperature	Normal、Warm、Cool
Backlight Adjustable	No
De-interlace	3D
Comb Filter	3D

SOUND

Speaker Power	10Wx2
Stereo	Yes ☐ -B

TERMINALS

input/output terminal	RJ45*1, VGA*1, PC Audio in*1, COAXIAL OUT*1, Audio in*1、Y(CVBS)PBPR*1 ,RF IN*1, HDMI*3 ■EARPHONE OUT ,USB*2

POWER

working Power consumption	≤115W
Stand by Power consumption	≤0.5W
AC Power Supply	AC100-240V,50/60Hz

Basic Equipped Accessories

Remote Control	HSC-TH1901
Batteries for RC	2xAAA
User Manual	Black and white，A5，28P，English
Other	
(Optional, Need to add cost)	☐EGL ☐QSG ☐POP ☐Warranty Card

Packaging Volume & Weight Data

	W (mm)	H (mm)	D (mm)	Number of Units	Gross Weight (kg)	Nett Weight (kg)	Vol (cbm)	20' qty	40' GP qty	40' HQ qty
Individual Gift Box								221	474	534
Outer Export Carton:	1185	723	138							