



**W43B22BT3D**

TV LED 43 CLASS SMART ISDBT WESTINGHOUSE 1+8 CON  
BLUETOOTH (A/M CON CONTROL DE VOZ)

**DISPLAY**

Backlight Type	DLED
Active Area	924.48 (H) × 506.52 (V)(43 class)
Aspect Ratio	16:9
Resolution	1920x1080
Refresh Rate	60Hz
Luminance	200 cd/m <sup>2</sup> ±10%
Contrast Ratio	4000:1
Display Colors	16.7M
Response Time	8ms
View Angle	176H/176V

**FEATURES**

Chipset	RT2842
OSD Language/OSD	English, French, German, Italian, Spanish, Portuguese
Sleep Timers	Yes
Auto Shut off	Yes
Hotel Mode	TBD
Max Storage Channels	ATV:AIR: 2-69 CABLE: 1-125, DTV ISDB-T:500CH,
HDMI Version/HDMI	1.4 HDCP Version:1.4 <input checked="" type="checkbox"/> CEC <input checked="" type="checkbox"/> ARC
USB Chanel Function/USB	SW Upgrade, Multimedia
Other function	EPG, Subtitle, CC <input type="checkbox"/> TELETXT <input type="checkbox"/> NICAM

**SMART SYSTEM**

CPU	ARM cortex -A55*4 1.1GHz
GPU	Mali470MP*3 600MHz
RAM	1GB
FLASH Memory	8GB
WIFI	2.4G,Support 802.11b/g/n
Ethernet	10M/100M
Android	9.0
App	Media Center, Zeasn

**TV SYSTEM**

TV Input	ATV/ISDB-T
Video System	ATV:NTSC DTV: MPEG-2 MP@ML_H.264
Sound System	ATV:M/N DTV:AAC, HE-AAC
Component Video Format	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
PC Video Format	1920*1080
HDMI Video Format	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Photo	jpeg/bmp/png/gif/mpo
Movie	avi/mpg/mov/ts/mkv/dat/mp4/vob
Music	mp3/aac/flac/arm/pcm
Subtitle	txt
DVD Combo Format/DVD	No

**Picture**

Color Temperature	Normal, Warm, Cool
Backlight Adjustable	No
De-interlace	3D
Comb Filter	3D

**SOUND**

Speaker Power	10Wx2
Stereo	Yes <input type="checkbox"/> -B

**TERMINALS**

input/output terminal	RJ45*1, (RCA)AV IN*1, VGA*1, RF IN*1, COAXIAL OUT*1, HDMI*3, USB*2, (RCA)YPBPR*1, EARPHONE OUT*1
-----------------------	--

**POWER**

working Power consumption	≤75W
Stand by Power consumption	≤0.5W
AC Power Supply	AC90-240V,50/60Hz

<b>Product Specifications</b>	
<b>Cosmetic</b>	
Color of Front Cabinet	Glossy Black+Concave
Color of Frame	N/A
Color of Middle Cabinet	Matte Black
Color of Back Cabinet	Matte Black
Color of Base Stand	Glossy Black
LED Indicator color/LED	RED (Standby) BLUE (ON)
Logo Indication/Logo	N/A
Number of Key	5 keys
VESA Wall Mounting Hole	200*200(mm)
Border Width	Top: 12, bottom: 20, Left: 12
power cable Length	1.5m, 2pin
Drop Standard	Chinese standard
<b>Material</b>	
Front Cover	plastic
Frame	N/A
Middle Cover	Metal
Back Cover	plastic
Stand	plastic
Carton	Brown corrugated Paper
Package	PO bag
Cabinet Request	<input checked="" type="checkbox"/> ROHS <input type="checkbox"/> VO FLAME RETARDATION
Certification	N/A
<b>Basic Equipped Accessories</b>	
Remote Control	RC057A
Batteries for RC	2xAAA
User Manual	Black and white, A5, 32P, English
<b>TERMINALS</b>	
input/output terminal	<input type="checkbox"/> EGL <input type="checkbox"/> QSG <input type="checkbox"/> POP <input type="checkbox"/> Warranty Card
<b>Product Info</b>	
EAN Bar code:	7453021617673
	W (mm) H (mm) D (mm)
Size of Unit (without Base):	951 541 88
Size of Unit (with Base):	951 588 218

<b>Packaging Volume &amp; Weight Data</b>										
	W (mm)	H (mm)	D (mm)	Number of Units	Gross Weight (kg)	Nett Weight (kg)	Vol (cbm)	20' qty	40' GP qty	40' HQ qty
Individual Gift Box										
Outer Export Carton:	1010	595	130					326	665	865